



Použití:



Standardní vrták k vrtání všech druhů ocelí, litiny a ocelolitiny, spékaného železa, alpacky, grafitu.

Usage:



The standard drill for the drilling of all types of steels, cast iron and cast steel, sintered iron, nickel-silver, graphite.

Applikation:



Standardbohrer zum Bohren aller Stahlsorten, Gusseisen und Stahlguss, Sintereisen, Neusilber, Graphit.

Применение:



Стандартные свёрла для сверления всех сортов стали, чугуна и стального литья, металлокерамических сплавов на основе железа, мельхиора, графита.

ϕd	l_1	l_2
2,00-2,12	49	24
2,13-2,36	53	27
2,37-2,65	57	30
2,66-3,00	61	33
3,01-3,35	65	36
3,36-3,75	70	39
3,76-4,25	75	43
4,26-4,75	80	47
4,76-5,30	86	52
5,31-6,00	93	57
6,01-6,70	101	63
6,71-7,50	109	69
7,51-8,50	117	75
8,51-9,50	125	81
9,51-10,60	133	87
10,61-11,80	142	94
11,81-13,20	151	101
13,21-14,00	160	108
14,10-15,00	169	114
15,10-16,00	178	120
16,10-17,00	184	125
17,10-18,00	191	130
18,10-19,00	198	135
19,10-20,00	205	140

TiN

TiCN

TiAlN



Příklad objednávky - Example of order - Bestellbeispiel - Пример заказа

$\phi d = 3,5$ DIN 338 RN HSS Co5

10015.0350