



**Závitové kruhové
čelisti
Circular dies
Schneideisen
Плашки**

UNC

Unifikovaný hrubý závit
Unified coarse thread
Unified-Grobgewinde
Унифицированная чёрная резьба



1,5P

	z/1"	P	D	h	S		code ^{*)}
4	40	0,635	20	5	3	2,8	XXX 004
5	40	0,635	20	5	3	3,1	XXX 005
6	32	0,794	20	7	3	3,4	XXX 006
8	32	0,794	20	7	3	4,1	XXX 008
10	24	1,058	20	7	3	4,7	XXX 010
12	24	1,058	20	7	4	5,4	XXX 012
1/4	20	1,270	20	7	4	6,2	XXX 140
5/16	18	1,411	25	9	4	7,8	XXX 516
3/8	16	1,588	30	11	4	9,4	XXX 380
7/16	14	1,814	30	11	5	10,95	XXX 716
1/2	13	1,954	38	14	5	12,5	XXX 120
9/16	12	2,117	38	14	5	14,1	XXX 916
5/8	11	2,309	45	18	5	15,7	XXX 580
3/4	10	2,540	45	18	6	18,8	XXX 340
7/8	9	2,822	55	22	5	22,0	XXX 780
1	8	3,175	55	22	6	25,1	XXX 100

^{*)} 215 XXX - NO / CS / WS

^{*)} 245 XXX - HSS

^{*)} 275 XXX - HSS s lamačem třísek / with spiral point / mit Schälanschnitt / с ломателем стружек

*Materiál: NO;
HSS, HSSE - dle požadavku
Provedení: závit lapovaný
Závit: pravý
Lícování: 2A*

*Material: CS;
HSS, HSSE - on request
Execution: lapped thread
Thread: right-hand
Tolerance: 2A*

*Werkstoff: WS;
HSS, HSSE - nach dem
Anspruch
Ausführung: geläpptes Gewinde
Gewinde: rechts
Toleranz: 2A*

*Material: NO;
HSS, HSSE - по заказу
Изготовлено: резьба
шлифованная
Резьба: правая
Подгонка: 2A*

