



**Závitové kruhové
čelisti
Circular dies
Schneideisen
Плашки**

UNF

Unifikovaný jemný závit
Unified fine thread
Unified-Feingewinde
Унифицированная мелкая резьба



1,5P

	z/1"	P	D	h	S		code ^{*)}
4	48	0,577	20	5	3	2,8	XXX 004
5	44	0,577	20	5	3	3,1	XXX 005
6	40	0,635	20	7	3	3,4	XXX 006
8	36	0,706	20	7	3	4,1	XXX 008
10	32	0,794	20	7	4	4,7	XXX 010
12	28	0,907	20	7	4	5,4	XXX 012
1/4	28	0,907	20	7	4	6,2	XXX 140
5/16	24	1,058	25	9	4	7,8	XXX 516
3/8	24	1,058	30	11	4	9,4	XXX 380
7/16	20	1,270	30	11	5	10,95	XXX 716
1/2	20	1,270	38	10	5	12,5	XXX 120
9/16	18	1,411	38	10	5	14,1	XXX 916
5/8	18	1,411	45	14	5	15,7	XXX 580
3/4	16	1,588	45	14	6	18,9	XXX 340
7/8	14	1,814	55	16	5	22,05	XXX 780
1	12	2,117	55	16	6	25,2	XXX 100

*) 216 XXX - NO / CS / WS

*) 246 XXX - HSS

*) 276 XXX - HSS s lamačem tříšek / with spiral point / mit Schälanschnitt / с ломателем стружек

Materiál: NO;
HSS, HSSE - dle požadavku
Provedení: závit lapovaný
Závit: pravý
Licování: 2A

Material: CS;
HSS, HSSE - on request
Execution: lapped thread
Thread: right-hand
Tolerance: 2A

Werkstoff: WS;
HSS, HSSE - nach dem
Anspruch
Ausführung: geläpptes Gewinde
Gewinde: rechts
Toleranz: 2A

Материал: NO;
HSS, HSSE - по заказу
Изготовлено: резьба
шлифованная
Резьба: правая
Подгонка: 2A

